



tesa[®] 4818

Product Information



Heat Seal Release Tape

Product Description

The pressure-sensitive adhesive tape consist of a PTFE-saturated glass cloth and a silicone adhesive.

Product Features

- low friction
- anti-stick properties on its surface
- It is is chemically, mechanically, and thermally resistant.

Application Fields

- Providing anti-stick properties to the equipment for heat sealing of films in packaging lines of various industries
- Masking applications above 200°C
- Gliding properties for material transportation

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------------|---------------------|----------|
| • Backing material | PTFE coated glass cloth | • Total thickness | 180 µm |
| • Type of adhesive | silicone | • Thickness of tape | _NULL µm |
| • Type of liner | none | | |

Properties/Performance Values

- | | | | |
|--------------------------------|-----------|--------------------------------|-------------------------------|
| • Elongation at break | 5 % | • Hand tearability | low |
| • Tensile strength | 310 N/cm | • Mesh | 108 threads/inch ² |
| • Abrasion resistance | very good | • Operation temperature up to | 260 °C |
| • Available as Spools | no | • Suitable for die cutting | yes |
| • Dielectric breakdown voltage | 4900 V | • Tensile strength (crosswise) | 490 N/cm |
| • Easy to remove | yes | • Unwind force n/cm | 4.5 N/cm |
| • Easy to write on | no | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 4.5 N/cm |
|---------|----------|



tesa[®] 4818

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04818>