



# tesa® 66200

## Product Information



tesa® 66200

### Product Description

tesa® 66200 is a black single-sided tape with a white foamed synthetic rubber adhesive. tesa® 66200 is designed to protect sensitive electronic components in Radar devices from environmental challenges like water, dust and dirt. It ensures an excellent Radar signal transmission through the tape and provides high bonding power on several plastics and metals.

### Product Features

- Low interference / reflection of radar signal (due to low DK and low tan delta)
- Puncture resistant backing
- Strong and permanent bonding on different relevant substrates like metals or metallized plastics
- Water resistance (like IPX9K)
- Easy die cutting

### Application Fields

Radar assembly and protection

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                  |                      |             |
|--------------------|------------------|----------------------|-------------|
| • Backing material | PET film         | • Colour             | black/white |
| • Type of adhesive | synthetic rubber | • Colour of liner    | transparent |
| • Type of liner    | PET              | • Thickness of liner | 50 µm       |
| • Total thickness  | 200 µm           |                      |             |

### Adhesion to Values

- steel 6.5 N/cm



# tesa<sup>®</sup> 66200

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=66200>