




tesa® 88710

Product Information



250µm Optically Clear Adhesive for Automotive Applications

Product Description

887xx Automotive OCA solution provides a wide thickness range together with outstanding ink step coverage feature and reliability performance.

It is a proven solution, well performed at glass/polarizer lamination stack-ups. And it would be suitable for a large and curved display lamination.

Product Features

- PSA type
- High transmission and low haze
- Smooth and easy liner removal
- High bonding strength
- Balanced gap filling and converting performance
- Excellent temperature, humidity and UV resistance

Application Fields

- Automotive Display Lamination
- Curved Glass
- Other optical integration

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	none	• Colour of liner - inside	transparent
• Type of adhesive	acrylic	• Colour of liner - outside	transparent
• Type of liner	PET	• Thickness of liner (easy release)	75 µm
• Colour	transparent	• Thickness of liner (tight release)	100 µm
• Colour of liner	transparent	• Thickness of tape	250 µm

Properties/Performance Values

• Ageing resistance (UV)	good	• Release of liner - outside	easy
• Haze <	0.001%	• Tack	good
• Humidity resistance	very good	• Temperature resistance long term duration	105 °C
• Release of liner - inside	tight	• Transmittance (380 - 780nm) >	99.5 %

For latest information on this product please visit <http://l.tesa.com/?ip=88710>



tesa[®] 88710

Product Information

Adhesion to Values

- Glass (initial) 8.5 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88710>