



tesa[®] Professional 4364

Product Information

2-in-1 solution for masking and covering

Product Description

tesa Easy Cover[®] 4364 combines a high value, folded special covering paper with a lightly crêped painter's tape and allows large areas to be covered and edges to be precisely taped off in just a single time-saving step. The smart 2-in-1 covering solution provides marked paint adherence and is also suited for sensitive, smooth and slightly rough surfaces during paint and plaster work. Professional painters use the 2-in-1 product among other things for taping off and protecting baseboards, window sills, window frames or door frames. Since the painter's tape is flexible, gentle curves can also be taped off.

Product Features

- Masking and protecting of large areas
- For clean, straight paint edges
- For smooth and slightly rough surfaces
- Ideal for covering windows during plastering and painting work
- For base boards, window sills, door and window frames etc.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|-------------------|--------|
| • Backing material | slightly-creped paper | • Total thickness | 140 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------------------|--------|
| • Elongation at break | 10 % | • Material of masking coverage | paper |
| • Tensile strength | 38 N/cm | • Suitable for rough surfaces | medium |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 3.4 N/cm |
|---------|----------|



tesa[®] Professional 4364

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?mp=04364>