



# tesa® 51616

## Product Information



Thick PET fleece tape for high noise damping

### Product Description

tesa® 51616 is a PET fleece wire harness tape with a rubber based adhesive.

Color: Black

### Product Features

- High noise damping
- High abrasion resistance
- Handtearable

### Application Fields

tesa® 51616 is designed for the passenger compartment, providing high noise damping.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Properties/Performance Values

- |   |         |                                   |                      |
|---|---------|-----------------------------------|----------------------|
| • Elongation at break                       | 50 %    | • Temperature resistance max.     | 105 °C               |
| • Tensile strength                          | 30 N/cm | • Temperature resistance min.     | -40 °C               |
| • Abrasion resistance (10mm mandrel, LV312) | Class D | • Unwind force (roll width < 9mm) | 12 N/roll (30 m/min) |
| • Abrasion resistance (5mm mandrel, LV312)  | Class C | • Unwind force (roll width > 9mm) | 12 N/roll (30 m/min) |
| • Noise damping (LV312)                     | Class D |                                   |                      |

### Adhesion to Values

- Steel 3 N/cm

### Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 7.5 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm

For latest information on this product please visit <http://l.tesa.com/?ip=51616>



# tesa<sup>®</sup> 51616

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51616>