



# 51057 PV50

## Product Information

tesa® hand-tearable PET cloth Spiralsleeve for abrasion protection and enhanced flexibility

## Product Description

tesa® Spiralsleeve 51057 PV50 is a hand-tearable PET cloth Sleeve®. It is produced with an advanced acrylic adhesive for spiral application. The adhesive-to-adhesive closure guarantees secure bonding.

## Product Features

- High temperature resistance 150°C/3000h
- High flexibility
- Hand-tearability
- Superior abrasion resistance
- Unique adhesive-to-adhesive closure system guarantees secure bonding without additional spot wraps

## Application Fields

tesa® Spiralsleeve 51057 PV50 is designed for the engine compartment, providing superior abrasion protection and flexibility.

It combines the well known spiral application of a tape with the flexibility of a tesa® Sleeve.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                                                      |      |
|--------------------|------------------|------------------------------------------------------|------|
| • Backing          | PET cloth        | • Total sustainable product content excluding liners | None |
| • Type of adhesive | advanced acrylic |                                                      |      |

## Product Assortment

- |                    |       |
|--------------------|-------|
| • Available colors | black |
|--------------------|-------|

## Properties/Performance Values

- |                                             |         |                               |         |
|---------------------------------------------|---------|-------------------------------|---------|
| • Abrasion resistance (10mm mandrel, LV312) | Class E | • Noise damping (LV312)       | Class B |
| • Abrasion resistance (5mm mandrel, LV312)  | Class E | • Temperature resistance max. | 150 °C  |
| • Hand tearability                          | yes     | • Temperature resistance min. | -40 °C  |

For latest information on this product please visit <http://l.tesa.com/?ip=51057>



# 51057

## PV50

### Product Information

#### Adhesion to Values

- Steel 3 N/cm

#### Additional Information

- Standard width: 35 mm
- Standard lengths: 15 m, 10 m
- Standard core diameter: 38 mm
- Additional dimensions on request
- Available as right- & left-hand version (35 mm)
- Color: black
- Minimum temperature while application: 15°C

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51057>