



tesa[®] 2410

Product Information



tesa[®] 2410 PV2 BOPP filmic tape for packaging

Product Description

Biaxially Oriented Polypropylene (BOPP) packaging tapes are pressure-sensitive adhesive strips made out of plastic used to close or seal packaging during storage or transit. Specifically, BOPP film is a thermoplastic polymer that it is malleable at certain temperatures but returns to a solid form when it is cooled down.

tesa[®] 2410 PV2 is a high performance BOPP packaging tape with a high-grade rubber adhesive. It is recommended for a strong packaging of cartons, made of recycled paper. Very high tack and strong bonding to various types of corrugated cartons, makes it an ideal all-purpose packaging tape.

Product Features

- Excellent dimensional stability, making these tapes shrink and wrinkle-proof
- High tensile strength in both cold and hot applications
- Non-toxic, recyclable and have excellent UV resistance
- High printability and does not cause color bleeding, fading, or spreading

Application Fields

- Food packaging, bundling and sealing
- Electrical applications, printing and lamination
- Extrusion coating, flower packing and reverse printing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 42 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|--------------------|--------|
| • Elongation at break | 50 % | • Hand tearability | medium |
| • Tensile strength | 24 N/cm | | |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 2 N/cm |
|---------|--------|

For latest information on this product please visit <http://l.tesa.com/?ip=02410>



tesa[®] 2410

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=02410>