



tesa[®] 60405

Product Information



tesa[®] 60405

Hard grade PVC closed cell double sided foam tape 4.8mm thick (black). Ideal for use in the glazing market

Product Description

tesa 60405 is a 4.8mm hard grade closed cell PVC foam tape with an acrylic adhesive on both sides. The closed cell foam can create a waterproof barrier when compressed, while still being flexible enough to seal uneven surfaces. The higher density foam has a greater resistance to water penetration than tesa 602 Series foam tapes, making it the ideal choice for sealing applications in the glazing market.

tesa 604 Series is resistant to fungi, oxidation, UV and ozone. It also complies with A.A.M.A.**810-85 type 1 and AS 2047 standards.

Note: 604 Series has a permanently elastic adhesive and is not suitable for bonding or mounting applications. The elastic adhesive prevents flanking, stopping the water passing between the foam and the glass or aluminium window frame.

Product Features

- The closed cell foam can create a waterproof barrier when compressed, while still being flexible enough to seal uneven surfaces.
- The higher density foam has a greater resistance to water penetration than tesa 602 Series foam tapes, making it the ideal choice for sealing applications in the glazing market.
- tesa 604 Series is resistant to fungi, oxidation, UV and ozone.
- It complies with A.A.M.A.**810-85 type 1 and AS 2047 standards.
- The elastic adhesive prevents flanking, stopping the water passing between the foam and the glass or aluminium window frame.

Application Fields

tesa 604 Series foam tape is an approved primary glazing seal for domestic and commercial glazing systems.

Application ideas:

- * Primary seal between the glass and metal frame in commercial and domestic windows and window walls

For latest information on this product please visit <http://l.tesa.com/?ip=60405>



tesa[®] 60405

Product Information

Application Fields

* Dampening vibrations between the metal frame and cladding in the transport industry

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	PVC foam	• Total thickness	4800 µm
• Type of adhesive	acrylic	• Color	black
• Type of liner	paper		

Properties/Performance Values

• Elongation at break	160 %
-----------------------	-------

Additional Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60405>