



# tesa<sup>®</sup> 69402

## Optically Clear Adhesive

### Product Information

50µm optically clear transfer tape

### Product Description

tesa<sup>®</sup> 69402 is a highly transparent transfer tape produced under controlled clean room conditions and designed for optically clear lamination.

### Product Features

- High transmission and low haze
- Excellent ITO compatibility
- Great whitening resistance
- Good temperature, humidity and UV resistance

### Application Fields

- Optically clear lamination of films to rigid or flexible substrates
- Bonding of touch panels to protective cover
- Lamination of optical films, e.g. protection film or anti-splinter film

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |             |                                    |             |
|--------------------|-------------|------------------------------------|-------------|
| • Backing          | none        | • Color of liner                   | transparent |
| • Type of adhesive | acrylic     | • Thickness of easy release liner  | 50 µm       |
| • Type of liner    | PET film    | • Thickness of tape                | 50 µm       |
| • Color            | transparent | • Thickness of tight release liner | 75 µm       |



# tesa<sup>®</sup> 69402

## Optically Clear Adhesive

Product Information

### Additional Information

50µm easy release PET liner outside of the roll

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=69402>