



tesa[®] 4576 High Barrier

Product Information

Venting tape



Product Description

tesa[®] 4576 is a highly elastic single sided adhesive tape. It consists of a PET/cellulose non-woven fabric coated with an acrylic adhesive.

Its high gas permeability through the adhesive and non woven carrier makes it the ideal barrier solution for any kind of foaming processes.

Features:

- gas permeable backing and adhesive
- low unwinding force
- conformable and elastic
- moisture resistant
- waterproof
- ageing-resistant

Application Fields

- Venting tape for foaming processes e.g. refrigerators
- Suitable for applications in the automotive industry, e.g. production of dashboards

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------|---------------------|----------|
| • Backing | non-woven | • Color | white |
| • Type of adhesive | acrylic | • Thickness of tape | _NULL µm |
| • Total thickness | 140 µm | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------------------------------------|-------------------------------|--------|
| • Elongation at break | 17 % | • Hand tearability | good |
| • Tensile strength | 10 N/cm | • Low unwinding force | good |
| • Ageing resistance (UV) | very good | • Operation temperature up to | 160 °C |
| • Air permeability | 6 cm ³ /cm ² xs | • Solvent free | yes |

Adhesion to Values

- | | | | |
|-----------------|----------|----------------|--------|
| • ABS (initial) | 2.2 N/cm | • PS (initial) | 2 N/cm |
| • PE (initial) | 0.8 N/cm | • Steel | 1 N/cm |

For latest information on this product please visit <http://l.tesa.com/?ip=04576>



tesa[®] 4576 High Barrier

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04576>