



# tesa<sup>®</sup> 64285 PV10



## Product Information

basic tensilised non-staining strapping tape

## Product Description

tesa<sup>®</sup> 64285 PV10 is a tensilized polypropylene strapping tape with a synthetic rubber adhesive system.

## Product Features

- high tensile strength
- low elongation

## Application Fields

tesa<sup>®</sup> 64285 PV10 is used in a wide variety of industrial applications with a focus on bundling- and palletizing applications

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                   |             |
|--------------------|------------------|-------------------|-------------|
| • Backing          | MOPP             | • Total thickness | 72 µm       |
| • Type of adhesive | synthetic rubber | • Color           | transparent |

## Properties/Performance Values

- |                       |          |                             |     |
|-----------------------|----------|-----------------------------|-----|
| • Elongation at break | 35 %     | • No discoloration          | yes |
| • Tensile strength    | 180 N/cm | • Residue-free removability | yes |

## Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 6 N/cm |
|---------|--------|



# tesa<sup>®</sup> 64285 PV10

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64285>