



# tesa<sup>®</sup> 4169

## Product Information



## Premium Soft PVC Floor Marking Tape

### Product Description

tesa<sup>®</sup> 4169 is an extremely robust high-performance adhesive tape for permanent floor markings. The abrasion-resistant, robust and resilient floor-marking tape comprises a soft PVC backing with an acrylate adhesive mass. Thanks to the , it can also be used on rough surfaces and is also suitable for curved applications. tesa<sup>®</sup> 4169 is available in the colors black, green, white, blue, red, yellow and black/yellow; the color combinations correspond to legally prescribed safety guidelines. Depending on its color, the floor-marking tape can be explicitly used as a warning tape.

<span class="ql-size-normal" style="color: rgb(51, 51, 51)

### Product Features

- Durable and abrasion resistant backing for permanent floor marking applications; hand tearable
- It has a high degree of flexibility which allows for curved applications
- Color combinations correspond to legally prescribed safety guidelines

### Application Fields

- tesa<sup>®</sup> 4169 is recommended for permanent marking for high-traffic areas, e.g. factories, warehouses, offices, or hospitals
- The premium floor marking tape can be used for the marking of working areas in workshops

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |          |                   |        |
|--------------------|----------|-------------------|--------|
| • Backing          | soft PVC | • Total thickness | 187 µm |
| • Type of adhesive | acrylic  |                   |        |

### Properties/Performance Values

- |                    |           |
|--------------------|-----------|
| • Tensile strength | 42.5 N/cm |
|--------------------|-----------|



# tesa<sup>®</sup> 4169

## Product Information

### Additional Information

The uni colours of tesa<sup>®</sup> 4169 are in accordance to the RAL color scheme.

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04169>