



tesa® 61623

Product Information



Basic Noise Damping Tape with PCR PET Backing

Product Description

tesa® 61623 is a rPET non-woven wire harness tape with a solvent-free rubber-based adhesive mainly used for wire harness covering in the passenger compartment. Thanks to its 80% PCR PET content in backing and solvent-free production process, tesa® 61623 is contributing to sustainability.

Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

Product Features

- 80% Recycled Content in Backing
- Solvent-free production process
- Solid noise damping performance
- Stable unwind force
- Ageing resistant up to 3000 h
- Excellent cable compatibility

Application Fields

tesa® 61623 is designed to provide solid noise damping and secure bundling performances on the harness. The tape is mainly applied on harnesses for the passenger compartment. The harness remains flexible after applying the tape.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---|-------------------|--------|
| • PET fleece | Bio-based carbon content of liner (acc. ASTM D6866) | • Total thickness | 250 µm |
| • Type of adhesive | rubber based | | |

Product Assortment

- | | |
|--------------------|-------|
| • Available colors | black |
|--------------------|-------|

For latest information on this product please visit <http://l.tesa.com/?ip=61623>



tesa[®] 61623

Product Information

Properties/Performance Values

- | | | | |
|---|---------|-----------------------------------|----------------------|
| • Elongation at break | 20 % | • Noise damping (LV312) | Class C |
| • Tensile strength | 45 N/cm | • Temperature resistance max. | 105 °C |
| • Abrasion resistance (10mm mandrel, LV312) | Class B | • Temperature resistance min. | -40 °C |
| • Abrasion resistance (5mm mandrel, LV312) | Class A | • Unwind force (roll width > 9mm) | 10 N/roll (30 m/min) |
| • Hand tearability | yes | | |

Adhesion to Values

- Steel 2 N/cm

Storage Conditions

Storage Conditions

- Storage temperature: 23°C (+/-10°C)
- Relative humidity: recommended 40–60% (room climate)
- Product guarantee: tesa guarantees a maximum shelf life of 12 months from date of dispatch (based on ISO 554)

Additional Information

- Standard width: 19 mm
- Standard lengths: 15, 25 m
- Standard core diameter: 38 mm
- Further dimensions only available upon request

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61623>