




tesa[®] 88708

Optically Clear Adhesive



Product Information

200µm Optically Clear Adhesive for Automotive Applications

Product Description

887xx Automotive OCA solution provides a wide thickness range together with outstanding ink step coverage feature and reliability performance.

It is a proven solution, well performed at glass/polarizer lamination stack-ups. And it would be suitable for a large and curved display lamination.

Product Features

- PSA type
- High transmission and low haze
- Smooth and easy liner removal
- High bonding strength
- Balanced gap filling and converting performance
- Excellent temperature, humidity and UV resistance

Application Fields

- Automotive Display Lamination
- Curved Glass
- Other optical integration

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

| | | | |
|---------------------------|-------------|------------------------------------|-------------|
| • Backing | none | • Color of liner - outside | transparent |
| • Type of adhesive | acrylic | • Thickness of easy release liner | 75 µm |
| • Type of liner | PET film | • Thickness of tape | 200 µm |
| • Total thickness | 200 µm | • Thickness of tight release liner | 100 µm |
| • Color | transparent | • Type of liner - inside | PET |
| • Color of liner | transparent | • Type of liner - outside | PET |
| • Color of liner - inside | transparent | | |



tesa[®] 88708

Optically Clear Adhesive

Product Information

Properties/Performance Values

| | | | |
|-----------------------------|-----------|------------------------------------|-----------|
| • Ageing resistance (UV) | very good | • Release of liner - outside | easy |
| • Haze | 0.001 % | • Tack | very good |
| • Humidity resistance | very good | • Temperature resistance long term | 105 °C |
| • Refractive index | 1.48 | • Transmittance (380 - 780nm) > | 99.5 % |
| • Release of liner - inside | tight | | |

Adhesion to Values

- Glass (initial) 8.2 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=88708>