



tesa[®] 4370

Product Information



8 weeks UV resistant polyethylene coated cloth tape

Product Description

tesa[®] 4370 is a 8 weeks UV-resistant cloth tape. It consists of a PE coated 70 mesh woven PET fabric backing and a black UV-blocker, coated with a pressure sensitive natural rubber adhesive. tesa[®] 4370 UV extra is suitable for long term protection of areas like window frames, facades, and other surfaces during plastering and painting in construction sites.

Features:

- 8 weeks UV resistant
- good adhesion, even on rough surfaces
- water repellent
- conformable
- easy to remove without residues
- easy to unwind
- available in white

Product Features

- It can be easily torn by hand both crossways and lengthways and offers impressive adhesive strength.
- Thanks to its high degree of UV resistance, the waterproof cloth duct tape can be used outdoors for up to 8 weeks at a time.
- tesa 4370 is very easy to handle and is your reliable partner for house building and other construction projects.
- High UV resistance (up to 8 weeks) and water-repellent
- Good adhesion even to rough surfaces
- Residue-free removability for masking applications
- Conformable and easy to unwind

Application Fields

- Bundling and strapping heavy goods * Suitable for application on concrete/bricks, timber, glass
- Marking of designated areas
- Various applications in construction and house building ... and a lot more!

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

For latest information on this product please visit <http://l.tesa.com/?ip=04370>



tesa[®] 4370

Product Information

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|--------------------------|
| • Elongation at break | 10 % | • Mesh | 70 count per square inch |
| • Tensile strength | 60 N/cm | • Suitable for rough surfaces | good |
| • Hand tearability | good | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.8 N/cm |
|---------|----------|

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04370>