



tesa® 51966

Product Information



200µm double sided transparent PET film tape with 90% PCR PET content in backing

Product Description

tesa® 51966 is a transparent double-sided industrial mounting tape with a 90% post-consumer recycled (PCR) PET backing and a highly tackified acrylic adhesive. The double-sided tape is especially designed for converter and tape specialist business and is able to withstand numerous environmental factors such as humidity, UV light and temperatures of up to 130°C for limited periods of time. The tackified acrylic adhesive provides excellent adhesion on various surfaces, very high tack, and good shear strength. tesa® 51966 contains an average of 8% post-consumer recycled content, consisting of 90% recycled PET backing. Liner and tape core are considered packaging materials and are excluded from recycled content calculations. This is a third-party environmental claim validated against the UL Environmental Claim Validation Procedure 2809 for recycled content. The UL Environmental Claim Validation Program falls under UL's ISO/IEC 17025 accreditation. Find more information on the UL SPOT® database https://spot.ul.com/main-app/products/detail/62a340de7501b678a13670cb?page_type=Products%20Catalog

Product Features

- Excellent combination of high initial tack and immediate adhesion
- Full suitability for long-term applications
- Outstanding converting properties

Application Fields

- Various industrial long-term mounting applications
- Especially designed for converter and tape specialist business

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-------------------------------------------------------|-------------------|-------------|
| • PET film | Bio-based carbon content of liner (acc. DIN EN 16640) | • Total thickness | 200 µm |
| | | • Color | transparent |
| • Type of adhesive | acrylic | | |



tesa[®] 51966

Product Information

Properties/Performance Values

• Elongation at break	55 %	• Static shear resistance at 23°C	good
• Tensile strength	20 N/cm	• Static shear resistance at 40°C	good
• Ageing resistance (UV)	good	• Tack	very good
• Chemical Resistance	good	• Temperature resistance long term	80 °C
• Humidity resistance	very good	• Temperature resistance min.	-40 °C
• Softener resistance	good	• Temperature resistance short term	130 °C

Adhesion to Values

• ABS (initial)	10.5 N/cm	• PET (after 14 days)	9.5 N/cm
• ABS (after 14 days)	11.5 N/cm	• PP (initial)	7.5 N/cm
• Aluminium (initial)	9 N/cm	• PP (after 14 days)	8 N/cm
• Aluminium (after 14 days)	10 N/cm	• PS (initial)	11 N/cm
• PC (initial)	13 N/cm	• PS (after 14 days)	12 N/cm
• PC (after 14 days)	13.5 N/cm	• PVC (initial)	9 N/cm
• PE (initial)	7 N/cm	• PVC (after 14 days)	13 N/cm
• PE (after 14 days)	7.5 N/cm	• Steel (initial)	10.5 N/cm
• PET (initial)	9 N/cm	• Steel (after 14 days)	11 N/cm

Additional Information

Liner variants:

- PV06: red MOPP film (80µm; 72g/m²)
- PV20: branded brown paper (69µm; 80g/m²)

According to VDA278 analysis, tesa 51966 does not contain any single substances restricted by the drafted GB regulations (China) as well as the indoor concentration guideline by Health, Labour and Welfare Ministry (Japan).

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51966>