



# tesa<sup>®</sup> 6089

## Product Information

Floor marking dispenser

### Product Description

The tesa 6089 floor Marking dispenser was especially designed for the convenient application of tesa 4169 Marking tape permanent and tesa 60760 Marking tape. The dispenser offers of a stable steel body. The height adjustable handlebar gives you convenient working conditions.

### Product Features

- The dispenser offers of a stable steel body.
- The height adjustable handlebar gives you convenient working conditions.

### Application Fields

You can use rolls up to 100m : 100mm. Changing of rolls is very easy and fast. A rubber pressure roll secures the save application even on slightly rough surfaces. The adjustable rear axis allows the marking even under challenging (space wise) conditions. The marking of fixed curves is easily possible. The marking of straight lines is supported by an optional laser guiding systems.

### Properties/Performance Values

- |                      |        |                  |         |
|----------------------|--------|------------------|---------|
| • Core diameter      | 3      | • Roll width max | 100 mm  |
| • Max. roll diameter | 170 mm | • Weight         | 20000 g |
| • Mode of drive      | manual |                  |         |

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=06089>