



51026 PV5



Product Information

PET cloth Sleeve for abrasion protection and enhanced flexibility

Product Description

tesa Sleeve® 51026 PV5 is a PET cloth Sleeve coated at the edges with an acrylic adhesive for spiral application.

Major Features:

- High temperature resistance 150°C/3000h
- High flexibility
- Exceptionally high abrasion resistance

Color: Black

Application Fields

tesa Sleeve® 51026 PV5 is designed for the engine compartment, providing superior abrasion protection and flexibility. It combines the well known spiral application of a tape with the flexibility of a sleeve

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------|-------------------|--------|
| • Backing | PET cloth | • Total thickness | 530 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|---|---------|-------------------------------|--------|
| • Abrasion resistance (10mm mandrel, LV312) | Class E | • Temperature resistance max. | 150 °C |
| • Abrasion resistance (5mm mandrel, LV312) | Class D | • Temperature resistance min. | -40 °C |
| • Noise damping (LV312) | Class B | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 5.5 N/cm |
|---------|----------|

Additional Information

Standard widths: 45, 59 mm

Standard lengths: 10, 15 m

- Most combinations of width and length are possible
- Standard core diameter: 38 mm

For latest information on this product please visit <http://l.tesa.com/?ip=51026>



51026

PV5

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51026>