



# tesa® 52332

## Product Information



Plate mounting in flexographic printing, especially corrugated board postprint

### Product Description

tesa® 52332 is specially designed for demanding plate mounting applications, especially where high adhesion is required and where plates are mounted permanently. This is often the case in corrugated board postprint where plates are commonly mounted to e.g. Mylar sheets and hung vertically when stored.

- tesa® 52332 is ageing resistant
- tesa® 52332 has an embossed PP-liner to prevent the formation of air bubbles during plate mounting

### Product Features

- The structured PP liner prevents the formation of air pockets during plate mounting.

### Application Fields

tesa® 52332 is a plate mounting tape for flexographic printing, especially well suited to permanent mounting applications in corrugated board postprint.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                   |                 |    |
|--------------------|-------------------|-----------------|----|
| • Backing          | soft PVC          | • Type of liner | PP |
| • Type of adhesive | tackified acrylic |                 |    |

### Properties/Performance Values

- |                      |     |
|----------------------|-----|
| • Thickness category | 300 |
|----------------------|-----|



# tesa<sup>®</sup> 52332

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52332>