




tesa® 60374

Product Information



100µm double sided black electrically conductive woven tape

Product Description

tesa® 60374 is a black double sided electrically conductive self adhesive tape. It consists of an electrically conductive woven backing and an electrically conductive acrylic adhesive.

tesa® 60374 features especially:

- * Enhanced electrical conductivity in XYZ-direction
- * Highly reliable and stable conductivity even after damp heat conditions
- * Good bonding strength
- * Excellent grounding performance at small bonding area
- * Tear resistant and very good dimensional stability
- * Black color

Product Features

- Enhanced electrical conductivity in XYZ-direction
- Highly reliable and stable conductivity even after damp heat conditions
- Good bonding strength
- Excellent grounding performance at small bonding area
- Tear resistant and very good dimensional stability

Application Fields

- EMC applications
- * Main board, FPC grounding
- * Antenna grounding
- * Electrostatic discharge applications



tesa[®] 60374

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	conductive woven	• Color	black
• Type of adhesive	conductive acrylic	• Color of liner	white/blue logo
• Type of liner	PE-coated paper	• Thickness of liner	120 µm
• Total thickness	100 µm		

Properties/Performance Values

• Contact resistance z-direction (initial)	0.01 Ohm / square inch	• Surface resistance x-y-direction (adhesive)	0.1 Ohm / square
• Release of liner	easy	• Temperature resistance short term	160 °C
• Static shear resistance at 40°C	very good		

Adhesion to Values

• Steel (initial)	5.7 N/cm	• Steel (after 14 days)	8.5 N/cm
-------------------	----------	-------------------------	----------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60374>