



# tesa® 61958 EasySplice FilmLine Black A



## Product Information

Double-sided splicing tape

## Product Description

tesa® 61958 is a double-sided integrated flying splice tape consisting of a PET backing and a modified synthetic rubber adhesive.

tesa® 61958 features especially

- Very high tack properties
- Very good adhesion values on PE and PP films
- Low splice thickness

The innovative tape composition includes the following functions:

- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- Reliable detection of splice position
- One adhesive strip with tailored peel off characteristics for a precise opening of the new reel after contact

Colour: Black

## Product Features

- Slit liner for the secure fixation of the top layer
- Robust polyester backing for secure splicing even at high web tension
- Double-sided black backing for optical detection of the splice at the reel stand or in following processes
- High tack properties and good adhesion on unpolar surfaces for excellent contact between expiring web and new reel
- One adhesive strip with tailored peel off characteristics for a precise opening of the new reel after contact

## Application Fields

tesa® 61958 is particularly suitable for:

- Flying splices with flexible packaging material, especially PE and PP films

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                  |                   |        |
|--------------------|------------------|-------------------|--------|
| • Backing          | PETP             | • Total thickness | 105 µm |
| • Type of adhesive | synthetic rubber | • Color           | black  |



# tesa<sup>®</sup> 61958 EasySplice FilmLine Black A

## Product Information

### Properties/Performance Values

- Elongation at break 60 %
- Tensile strength 70 N/cm
- Shelf life time (packed) < 25°C 18 months

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=61958>