



tesa[®] 4830

Product Information



PTFE tape with a silicone adhesive

Product Description

tesa[®] 4830 is a premium single sided PTFE tape with silicone adhesive. This product is a self-adhesive and high performance tape for demanding applications, in which high temperature resistance, very good release properties and abrasion resistance is needed.

Features:

- * Excellent release properties due to PTFE surface and its low surface energy
- * Special silicone adhesive with well-balanced properties: Excellent adhesion level, residue free removable, no oozing at the edges
- * Smooth surface with low friction coefficient
- * Enhanced mechanical stability and abrasion resistance
- * Tensilized material for high tensile strength
- * Excellent temperature resistance
- * Superior resistance against chemicals and solvents

Product Features

- Excellent release properties due to PTFE surface and its low surface energy
- Special silicone adhesive with well-balanced properties: Excellent adhesion level, residue free removable, no oozing at the edges
- Smooth surface with low friction coefficient
- Enhanced mechanical stability and abrasion resistance
- Tensilized material for high tensile strength
- Excellent temperature resistance
- Superior resistance against chemicals and solvents

Application Fields

- Belt realization to avoid the just extruded PE edges sticking on the cylinders by laminating tesa[®] 4820 and tesa[®] 4830 together
- * Cylinder wrapping on the extrusion coating line next to the hole of the caps
- * High temperature, low friction, anti-stick properties for high end requirements

For latest information on this product please visit <http://l.tesa.com/?ip=04830>



tesa[®] 4830

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------|-------------------|--------|
| • Backing | PTFE film | • Total thickness | 160 µm |
| • Type of adhesive | silicone | • Color | brown |

Properties/Performance Values

- | | | | |
|-----------------------|----------|----------------------------|-----------|
| • Elongation at break | 150 % | • Abrasion resistance | very good |
| • Tensile strength | 220 N/cm | • Suitable for die cutting | yes |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.5 N/cm |
|---------|----------|

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04830>