



# tesa<sup>®</sup> 51003

## Product Information



### Aluminium detection label

#### Product Description

tesa<sup>®</sup> 51003 is a single sided oblong label consisting of an aluminium foil laminated to a white wood-free printing paper and a modified acrylic adhesive.

tesa<sup>®</sup> 51003 features especially

- Excellent adhesive performance
- High initial tack
- Reliable inductive detection

#### Product Features

- Excellent adhesive performance
- High initial tack
- Reliable inductive detection

#### Application Fields

tesa<sup>®</sup> 51003 is used for the inductive detection of the splice particularly in the printing and converting industry

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Product Construction

- |                   |                  |                      |                     |
|-------------------|------------------|----------------------|---------------------|
| • Backing         | Aluminised paper | • Color              | silver              |
| • Type of liner   | glassine         | • Thickness of liner | 57 µm               |
| • Total thickness | 78 µm            | • Weight of liner    | 62 g/m <sup>2</sup> |

#### Additional Information

Dimension per label: 99 mm x 45 mm

Pieces per roll: 1000



# tesa<sup>®</sup> 51003

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51003>