

tesa® Professional 60022

Product Information

Spray glue EXTRA STRONG, 500ml

Product Description

tesa® Spray Glue EXTRA STRONG 60022 is an extra strong, film-forming glue for permanently bonding materials such as fabric, plastic, cardboard, foam rubber, insulating materials, vinyl, leather, faux leather and rubber to each other or to metal and wood.

- Minimal spray mist, resistant to dampness and temperatures up to 80°C, short term 100°C
- Suitable for light as well as heavy materials with smooth to rough surfaces
- · High bonding range
- · Nozzle can be adjusted to desired spray quantity (H: high, M: Medium, L: Low)
- · Spray direction can be set to either horizontal or vertical
- · Particularly suitable for automotive applications
- · Free from silicone

Product Features

tesa® Spray Glue EXTRA STRONG 60022 is an extra strong, film-forming glue for permanently bonding materials such as fabric, plastic, cardboard, foam rubber, insulating materials, vinyl, leather, faux leather and rubber to each other or to metal and wood.

Application Fields

tesa® Spray Glue 60022 EXTRA STRONG is typically used for versatile bonding of demanding materials like foam and fabric and is typically used by

- upholsterers
- saddlers
- · automotive application

and many other professional applications in industry and craft. Furthermore, tesa® 60022 EXTRA STRONG is suitable for the general use at home.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Silicone free yes



tesa® Professional 60022

Product Information

Properties/Performance Values

•	Adhesive strength	High adhesion	•	Reusable	no
•	Applicationfield	Home, Office	•	Solvent free	no
•	Batteries included	no	•	Suitable for children of 3 years	no
•	Batteries required	no		of age	
•	Chemical Resistance	yes	•	Suitable surfaces	Even wood, Stone,
•	Compostable	no			Brick, Acrylic glass
•	Ecofriendly packaging	no	•	Temperature resistance	yes
•	Hazard material	yes	•	Temperature resistance max.	80 °C
•	Humidity resistance	yes	•	Temperature resistance min.	-30 °C
•	Recommended distance of	30 cm	•	UV resistant	yes
	spraying		•	Washable	no
•	Residue-free removability	no	•	Waterproof	yes

Additional Information

- tesa offers two complementary Spray Glues: 60021 PERMANENT and 60023 REPOSITIONABLE
- Observe the safety-information on the spray-can
- Shake can well before use and remove any dried-on glue from the nozzle
- · For new applications, test suitability by gluing a sample
- The parts to be bonded must be dry and free from dust and grease. We recommend cleaning with tesa® INDUSTRY CLEANER 60040
- · After use, turn can upside-down and expel glue from nozzle until only propellant comes out
- Overspray from Spray Glues can easily be removed with tesa® 60042 ADHESIVE REMOVER
- Refer to special instructions/safety data sheets: www.tesa.com/safety

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

