



tesa® 51616 ID

Product Information



Thick PET fleece tape for high noise damping with identifier solution

Product Description

tesa® 51616 ID is a PET fleece wire harness tape with a rubber based adhesive.

Color: Black with identifier

Product Features

- High noise damping
- High abrasion resistance
- Hand-tearable
- Identifier solution

Application Fields

tesa® 51616 ID is designed for the passenger compartment, providing high noise damping.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------|-------------------|--------|
| • Backing | PET fleece | • Type of liner | PP |
| • Type of adhesive | rubber based | • Total thickness | 650 µm |

Product Assortment

- | | |
|--------------------|---------------|
| • Available colors | black / white |
|--------------------|---------------|

Properties/Performance Values

- | | | | |
|---|---------|-----------------------------------|----------------------|
| • Elongation at break | 35 % | • Hardness | medium |
| • Tensile strength | 30 N/cm | • Noise damping (LV312) | Class D |
| • Abrasion resistance (10mm mandrel, LV312) | Class D | • Temperature resistance max. | 105 °C |
| • Abrasion resistance (5mm mandrel, LV312) | Class C | • Temperature resistance min. | -40 °C |
| • Color of logo | purple | • Unwind force (roll width < 9mm) | 12 N/roll (30 m/min) |
| • Hand tearability | yes | • Unwind force (roll width > 9mm) | 12 N/roll (30 m/min) |

For latest information on this product please visit <http://l.tesa.com/?ip=NaN>



tesa[®] 51616 ID

Product Information

Adhesion to Values

- Steel 3 N/cm

Storage Conditions

Storage Conditions

- Storage temperature: 23°C (+/-10°C)
- Relative humidity: recommended 40–60% (room climate)
- Product guarantee: tesa guarantees a maximum shelf life of 12 months from date of dispatch (based on ISO 554)

Additional Information

- Standard width: 19 mm
- Standard length: 10 m
- Standard core diameter: 38 mm

Further dimensions are available upon request

Elongation at break value depicts the minimum value.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=NaN>