



tesa[®] Professional 4169 PV3



Product Information

Floor Marking Tape Premium

Product Description

tesa[®] 4169 PV3 marking tape is UV resistant and due to the thick backing it is able to withstand high mechanical stress. It is perfect suitable for permanent marking applications.

Application Fields

- Marking of working areas e. g. in factories and warehouses.
- Guiding lines for mark sensitive vehicles e. g. transport robots.
- Marking of parking spaces and gangways in offices, hospitals, at fairs etc..

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------|-------------------|--------|
| • Backing | soft PVC | • Total thickness | 180 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|-----------|-------------------------------|------|
| • Elongation at break | 200 % | • Fluorescent | no |
| • Tensile strength | 30 N/cm | • Fogging | good |
| • Abrasion resistance | very good | • Hand tearability | good |
| • Ageing resistance (UV) | good | • Humidity resistance | good |
| • Easy to remove | no | • Suitable for rough surfaces | good |
| • Easy to write on | no | • Water resistance | good |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 1.8 N/cm |
|---------|----------|



tesa[®] Professional 4169 PV3

Product Information

Additional Information

The uni colours of tesaflex[®] 4169 PV3 are according to the RAL colour scheme.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04169>