



tesa[®] 51627

Product Information



PA velour tape for high noise damping

Product Description

tesa[®] 51627 is a thick PA velour wire harness tape with an acrylic based adhesive.

Major Features:

- * Temperature resistance 125°C/3000h
- * Exceptionally high noise damping
- * Very abrasion resistant

Color: Black

Product Features

- Temperature resistance 125°C/3000h
- Exceptionally high noise damping
- Very abrasion resistant

Application Fields

tesa[®] 51627 is designed for the engine compartment, providing high noise damping as well as high abrasion protection.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------|-------------------|---------|
| • Backing | PA velour | • Total thickness | 1000 µm |
| • Type of adhesive | acrylic | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51627>



tesa[®] 51627

Product Information

Properties/Performance Values

- | | | | |
|---|---------|-------------------------------|---------|
| • Abrasion resistance (10mm mandrel, LV312) | Class E | • Noise damping (LV312) | Class E |
| • Abrasion resistance (5mm mandrel, LV312) | Class E | • Temperature resistance max. | 125 °C |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 3.1 N/cm |
|---------|----------|

Additional Information

Standard lengths: 5, 7.5, 20m

Standard widths: 19, 25mm

* Further dimensions only available upon request

* Standard core diameter: 38mm

* Technical data acc. to LV 312

* Applicable for red ring assembly aid

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51627>