




tesa[®] 60250

Product Information



tesa[®] 60250 30 μ m double sided high appearance quality electrically conductive woven tape

Product Description

tesa[®] 60250 is a gray double-sided electrically conductive self-adhesive tape. It consists of an electrically conductive woven backing and an electrically conductive acrylic adhesive.

Product Features

- Superior appearance quality
- Excellent electrical conductivity
- Good bonding strength

Application Fields

- Grounding in OLED display module
- Grounding where appearance needs to be controlled during processing

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|--------------------|----------------------|------------|
| • Backing | conductive woven | • Color | grey |
| • Type of adhesive | conductive acrylic | • Color of liner | white |
| • Type of liner | PET film | • Thickness of liner | 50 μ m |
| • Total thickness | 30 μ m | | |

Properties/Performance Values

- | | | | |
|--|------------------------|---|------------------|
| • Contact resistance z-direction (initial) | 0.05 Ohm / square inch | • Surface resistance x-y-direction (adhesive) | 0.2 Ohm / square |
| • Release of liner | easy | | |

Adhesion to Values

- Steel (after 14 days) 7.8 N/cm



tesa[®] 60250

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60250>