



Product Information



$85 \ \mu m \ PCR-PET$ tape for Electrical Insulation applications

Product Description

tesa[®] 58352 is a blue 85 μm PCR-PET tape with a water-based acrylic adhesive. tesa[®] 58352 has been designed for electrical insulation applications in EV batteries.

Sustainable Aspects



For more information: https://www.tesa.com/product-sustainability

Product Features

- Dielectric breakdown and leakage current protection
- Anti-Repulsion performance
- Reworkability

Application Fields

- Cell-Wrapping
- Metal-Part Insulation

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

 Backing Bio-based carbon content of liner (acc. DIN EN 16640) Type of adhesive Bio-based carbon content of liner (acc. DIN EN 16640) 	PET film 90 % water-based acrylic 30 %	 Type of liner Total thickness Color of liner Thickness of liner 	PET film 85 μm transparent 23 μm
Properties/Performance Values			
Elongation at breakTensile strengthBreakdown voltage	80 % 50 N/cm 7 KV	CTI (adhesive side)CTI (backing side)Liner removal force	600 V 400 V 40 cN/cm





Product Information

Adhesion to Values

• Steel

4.5 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 30/08/24 – en-SG