



tesapack[®] 6300

Hand Dispenser Economy

Product Information

Dispenser ECONOMY for packaging tapes

Product Description

The tesa[®] 6300 hand dispenser is a good value dispenser for professional sealing of all kind of tesa[®] packaging tapes in packaging and production areas. The dispenser has a tension control so that even easy unwinding tesa[®] tapes can be used without difficulty. The blade is covered with a top to prevent injuries.

Product Features

- The dispenser has a tension control so that even easy unwinding tesa[®] tapes can be used without difficulty.
- The blade is covered with a top to prevent injuries.

Application Fields

Place the dispenser on the carton and pull it towards yourself. The contact roller presses the tape down firmly as it is applied from the roll. The tape is cut by the serrated blade by tilting the dispenser. The cut end of the tape is pressed to the carton by the flexible application plate. Threading: The tesa[®] roll is put on the tape wheel such that the adhesive side of the tape faces the handle. Pull the end of the tape between the tape guide roller and the metal plate until the tape is free of wrinkles.

Properties/Performance Values

• Adhesive strength	_NULL	• Roll width max	55 mm
• Applicationfield	Home, Office	• Serrated blade	no
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Spare part service	no
• Low noise unwinding	_NULL	• Suitable surfaces	_NULL
• Material	Metal	• Tear resistance	_NULL
• Max roll length	66 m	• Tension control	yes
• Max. core diameter	3	• Writable	no
• Reusable	yes		



tesapack[®] 6300

Hand Dispenser Economy

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=06300>