



tesa[®] 7496

Product Information

Premium Strength Tear Tape

Product Description

Our strongest tensilized polypropylene backing with natural rubber adhesive. General-purpose tear tape has good initial tack, excellent shear resistance, and strong ultimate adhesion.

Available in a variety of lengths and widths for application flexibility. Available Colors: White

Application Fields

- Heavy-duty tear tape for corrugated and solid board applications
- Handle and package reinforcement
- Durable surface protection

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|----------|
| • Backing | TPP | • Total thickness | 172.5 µm |
| • Type of adhesive | natural rubber | | 6.8 mils |

Properties/Performance Values

- | | | | |
|-----------------------|------|--------------------|------------------------|
| • Elongation at break | 35 % | • Tensile strength | 450 N/cm
257 lbs/in |
|-----------------------|------|--------------------|------------------------|

Adhesion to Values

- | | |
|---------|----------------------|
| • Steel | 5 N/cm
45.7 oz/in |
|---------|----------------------|



tesa[®] 7496

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=07496>