



tesa[®] 4263 PV0



Product Information

General purpose carton sealing tape

Product Description

tesa[®] 4263 features a film backing with a synthetic rubber adhesive. tesa[®] 4263 is perfect for hand dispensers and automatic sealing equipment.

Application Fields

Manual and automatic sealing of light and medium-range weight cartons.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------------|
| • Backing | PP film | • Total thickness | 47.5 μ m |
| • Type of adhesive | natural rubber | | 1.9 mils |

Properties/Performance Values

- | | | | |
|-----------------------|-------------------------|----------------------|-----|
| • Elongation at break | 140 % | • Manual application | yes |
| • Tensile strength | 45.53 N/cm
26 lbs/in | | |

Adhesion to Values

- | | |
|---------|-----------------------|
| • Steel | 5.25 N/cm
48 oz/in |
|---------|-----------------------|



tesa[®] 4263 PV0

Product Information

Additional Information

Available colors: white, tan, and transparent

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04263>