



tesa[®] 50537

Product Information



Temporary hood fixation tape for glass surfaces

Product Description

tesa[®] 50537 consists of a synthetic fleece backing coated with an synthetic elastomer adhesive.

Product Features

- Thick and robust fleece material
- Can be fixed by sewing to all sorts of material
- Reliable adhesion to glass with traceless removal
- UV resistant for outdoor use
- Suitable for die cutting

Application Fields

- Temporary hood fixation tape for glass surface

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------|--------|-------------------|-------------------------|
| • Backing | fleece | • Total thickness | 170 μ m
6.7 mils |
|-----------|--------|-------------------|-------------------------|

Properties/Performance Values

- | | | | |
|-----------------------|------|----------------------------|-----|
| • Chemical Resistance | good | • Suitable for die cutting | yes |
| • Easy to remove | yes | | |

Adhesion to Values

- | | |
|---------|------------------------|
| • Steel | 2.5 N/cm
22.8 oz/in |
|---------|------------------------|



tesa[®] 50537

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50537>