



# tesa<sup>®</sup> 52330

## Product Information



380 µm/15 mils plate mounting tape for flexographic printing, especially corrugated postprint

### Product Description

tesa<sup>®</sup> 52330 is a double-sided tape of 380 µm (15 mil) thickness with a cloth backing and a rubber adhesive. The product design makes this tape especially suitable for corrugated postprint plate mounting, where the tape is first applied to the printing plate, then the liner is removed and the plate is attached to the carrier film. The cloth backing provides a high degree of flexibility, facilitating easy plate mount, while the well-proven adhesive ensures a reliable yet removable bond between printing plate and carrier film. The unique liner structure prevents air trapping during plate mounting.

### Product Features

- The cloth backing provides a high degree of flexibility, facilitating easy plate mount, while the well-proven adhesive ensures a reliable yet removable bond between printing plate and carrier film.
- The unique liner structure prevents air trapping during plate mounting.

### Application Fields

Plate mounting in flexo printing, especially mounting of photopolymer plates on polyester carrier films for corrugated board postprint

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                 |              |
|--------------------|----------------|-----------------|--------------|
| • Backing          | cloth          | • Type of liner | creped paper |
| • Type of adhesive | natural rubber |                 |              |

### Properties/Performance Values

- |                      |     |
|----------------------|-----|
| • Thickness category | 380 |
|----------------------|-----|



# tesa<sup>®</sup> 52330

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52330>