



tesa® 51036 ORCN



Product Information

Flag-resistant PET cloth tape for high abrasion protection of automotive harnesses

Product Description

tesa® 51036 is a flag-resistant PET cloth wire harness tape with a solvent-free, advanced acrylic adhesive (triple A®). With the new adhesive formula, tesa® 51036 is highly resistant to flagging and ensures secure closure. tesa® 51036 provides excellent abrasion protection of automotive harnesses and withstands high temperatures and demanding environmental conditions.

Its acrylic adhesive is compatible with halogen-free cable jacketing materials (PE/PP) and guarantees enhanced durability.

Main features:

- High abrasion resistance
- High temperature resistance
- Flag-resistant
- Excellent cable compatibility
- Resistant to aging
- Can withstand environmental influences
- Can be used for manual and automatic application
- Flame-retardant
- Halogen-free
- Tear-resistant
- Constant unwind force
- Flexible and smooth
- Available in black and orange

Application Fields

tesa® 51036 has been specially designed for bundling and wire protection against abrasion. The main application field is the engine compartment of a car, with demanding temperature-related and environmental conditions.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------------|-------------------|-----------|
| • Backing | PET cloth | • Total thickness | 260 µm |
| • Type of adhesive | advanced acrylic | | 10.2 mils |

For latest information on this product please visit <http://l.tesa.com/?ip=51036>



tesa[®] 51036 ORCN

Product Information

Properties/Performance Values

- | | | | |
|---|------------|-----------------------------------|----------------------|
| • Elongation at break | 40 % | • Temperature resistance max. | 150 °C |
| • Tensile strength | 275 N/cm | | 302 °F |
| | 157 lbs/in | • Temperature resistance min. | -40 °C |
| • Abrasion resistance (10mm mandrel, LV312) | Class D | | -40 °F |
| • Abrasion resistance (5mm mandrel, LV312) | Class D | • Unwind force (roll width < 9mm) | 11 N/roll (30 m/min) |
| • Noise damping (LV312) | Class A | • Unwind force (roll width > 9mm) | 11 N/roll (30 m/min) |

Adhesion to Values

- | | |
|---------|------------|
| • Steel | 5 N/cm |
| | 45.7 oz/in |

Additional Information

Standard widths: 9, 19, 25, 32 mm

Standard lengths: 25 m

- Most combinations of width and length are possible
- Further dimensions are available upon request
- Standard core diameter: 38 mm
- Applicable for red ring assembly aid
- Minimum temperature while application: 15°C/59°F
- Elongation at break of 51036 orange: 45%

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51036>