




tesa[®] ACXplus 77208

Product Information



0.8mm double-sided acrylic foam tape

Product Description

tesa[®] ACX^{plus} 77208 is a single layer acrylic foam tape designed for automotive attachment parts. Its viscoelastic acrylic foam core achieves reliable and high bonding performance on a variety of substrates and can withstand changing environmental conditions throughout the lifetime of a vehicle.

Features:

- Viscoelastic acrylic foam core compensates stress caused by different thermal elongation of bonded parts
- Good dynamic and static shear resistance over a wide temperature range
- High UV resistance
- Good converting properties

Application Fields

Permanent exterior mounting:

- Body side moldings and decorative trims
- Emblems
- Spoilers
- Antennas
- Pillar appliqués

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------------------|
| • Backing | foamed acrylic | • Total thickness | 800 µm |
| • Type of adhesive | pure acrylic | • Color | 31.5 mils
gray |

Properties/Performance Values

- | | | | |
|--------------------------|-----------|---------------------|--------------|
| • Ageing resistance (UV) | very good | • Temperature range | -40 to 80 °C |
| • Humidity resistance | good | | |

Adhesion to Values

- | | | | |
|----------------------|-----------------------|------------------------|------------------------|
| • ABS (after 3 days) | 10 N/cm
91.4 oz/in | • Steel (after 3 days) | 24 N/cm
219.3 oz/in |
|----------------------|-----------------------|------------------------|------------------------|

For latest information on this product please visit <http://l.tesa.com/?ip=77208>



tesa[®] ACXplus 77208

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=77208>