



tesa[®] 4244 PV0



Product Information

Fineline tape for design painting in the automotive paint shop

Product Description

tesa[®] 4244 PV0 is a flexible soft PVC tape with a natural rubber adhesive for fineline masking if a very sharp paint edge is required, especially on painted or unpainted plastic parts. The 110 µm/4.33 mils thickness helps to implement good and sharp paint edges, while the soft PVC of the tapes offers good conformability.

With a temperature resistance of 140°C/284°F for 1h, tesa[®] 4244 PV0 is targeting mid-temperature masking applications, such as car bumper masking.

Standardized and customized applicators for tesa[®] 4244 PV0 are available to ensure efficient tape application.

Main features:

- Temperature resistance of up to 140°C/284°F for 1h
- Conformability with the dimensional change during oven drying
- Good conformability with multidimensional surfaces
- Edge does not lift off and residue-free removal

Application Fields

tesa[®] 4244 PV0 is suitable for various types of masking applications.

Example applications are:

- Car bumper masking applications
- Masking applications in tight and narrow curves and difficult 3-D shapes
- Masking with special requirements in regard to PVC or halogen usage

To ensure the highest performance possible, our aim is to fully understand your application (including the substrates involved) in order to provide the right product recommendation.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|----------|
| • Backing | PVC film | • Total thickness | 110 µm |
| • Type of adhesive | natural rubber | | 4.3 mils |

For latest information on this product please visit <http://l.tesa.com/?ip=04244>



tesa[®] 4244 PV0

Product Information

Properties/Performance Values

- | | | | |
|-----------------------|------------------------|----------------------------|-----------|
| • Elongation at break | 237 % | • Flame retardance | very good |
| • Tensile strength | 27 N/cm
15.4 lbs/in | • Hand tearability | very good |
| • Easy to remove | yes | • Suitable for die cutting | yes |

Adhesion to Values

- | | |
|---------|------------------------|
| • Steel | 3.7 N/cm
33.8 oz/in |
|---------|------------------------|

Additional Information

tesa[®] 4244 is also available for converting and die-cutting with a paper liner 4244 PV4:
adhesion to steel = 4,7 N/cm, 42.9 oz/in
peel off force from liner = 14 cN/cm, 1.3 oz/in
die cuts are available as tesa[®] 54244

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04244>