



tesa[®] 53313

Product Information

Performance-Grade Kraft Flatback Tape with a blend of Natural and Synthetic Rubber Adhesive

Product Description

tesa[®] 53313 is a kraft paper flatback tape with a blend of natural and synthetic rubber adhesive systems for all around excellent performance. The tape performs exceptionally in a wide range of temperatures and humidity conditions for your various application needs. Provides superior holding power and shear resistance in splicing and core starting applications. Available Colors: Tan

Application Fields

- Non-repulpable splicing, core starting, and end tabbing
- Heavy-duty carton sealing applications
- Meets CID A-A-883B Type II specification

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------------------|---------------------|--------------------|
| • Backing | Paper | • Color | brown |
| • Type of adhesive | natural & synthetic rubber | • Thickness of tape | 190 µm
7.5 mils |
| • Total thickness | 190 µm
7.5 mils | | |

Properties/Performance Values

- | | | | |
|-----------------------|-----|--------------------|------------------------|
| • Elongation at break | 7 % | • Tensile strength | 79 N/cm
45.1 lbs/in |
|-----------------------|-----|--------------------|------------------------|

Adhesion to Values

- | | |
|---------|------------------------|
| • Steel | 6.2 N/cm
56.6 oz/in |
|---------|------------------------|



tesa[®] 53313

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=53313>