

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

Page 1/11

1 Identification · Product identifier · Trade name tesa 60152 · Application of the substance / the mixture Coating material Priming Intermediate · Manufacturer/Supplier: tesa SE Tel.: +49-40-88899-101 Hugo-Kirchberg-Str. 1 D-22848 Norderstedt Germany · Informing department: tesa SE, Corporate Regulatory Affairs SDS@tesa.com, Tel.: +49-40-88899-6954 · Emergency telephone number: **Reception Headquarters** tesa SE, Hugo-Kirchberg-Str. 1, 22848 Norderstedt, Germany Phone: +49 40 88899 2667 (Mon.-Thurs. 07:00-18:00h, Fr. 07:00-15:00h)

Classification of the substar	nce or mixture
GHS02 Flame	
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
GHS08 Health haza	ard
Carcinogenicity 1A	H350 May cause cancer.
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.
GHS07	
Skin Irritation 2	H315 Causes skin irritation.
Specific Target Organ Toxicity	- Single Exposure 3 H336 May cause drowsiness or dizziness.
Label elements GHS label elements	The product is classified and labeled according to the Globally Harmonized Syste (GHS).
Hazard pictograms	
	GHS02 GHS07 GHS08
Signal word	Danger
Hazard-determining compor labeling:	nents of ethanol Naphtha (petroleum), hydrotreated light (Note P)
Hazard statements	Highly flammable liquid and vapor.
	Causes skin irritation. May cause cancer.



Page 2/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

	(Contd. of page 1
	May cause drowsiness or dizziness.
	May be fatal if swallowed and enters airways.
Precautionary statements	Keep away from heat/sparks/open flames/hot surfaces No smoking.
	Use only outdoors or in a well-ventilated area.
	If swallowed: Immediately call a poison center/doctor.
	Specific treatment (see on this label).
	Do NOT induce vomiting.
	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin wit
	water/shower.
	Take off contaminated clothing and wash it before reuse.
	Store locked up.
	Dispose of contents/container in accordance with local/regional/national/international
	regulations.
Classification system	
NFPA ratings (scale 0-4)	Health = 1
	3 Fire = 3
	(1×0) Reactivity = 0
HMIS ratings (scale 0-4)	HEALTH *1 Health = *1
	FIRE 3 Fire = 3
	Reactivity = 0
Other hazards	The product does not contain any elutable organically bound halogen compound
	which may lead to an increase in the AOX value during wastewater analysis.
Results of PBT and vPvB asse	
PBT:	Not applicable.
vPvB:	Not applicable.

				<u> </u>	
N I	 	 	841		

· Chemical characterization: wixtures	j
· Description:	S

Solvent mixture with additives. Lösung von Polyamid in Benzin und Ethanol

64-17-5		<50%
	 Flammable Liquids 2, H225 Carcinogenicity 1A, H350 	
	Naphtha (petroleum), hydrotreated light (Note P) Flammable Liquids 2, H225 Aspiration Hazard 1, H304 Skin Irritation 2, H315; Specific Target Organ Toxicity - Single Exposure 3, H336	<50%

4 First-aid measures

- · Description of first aid measures
- · General information
- · After inhalation
- · After skin contact · After eye contact
- In case of unconsciousness bring patient into stable side position for transport.

Instantly remove any clothing soiled by the product.

- Instantly wash with water and soap and rinse thoroughly.
- Rinse opened eye for several minutes under running water. Consult a doctor if symptoms persist After swallowing

(Contd. on page 3)

-US-



Page 3/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

	(Contd. of page 2
 Information for doctor 	
• Most important symptoms and	
effects, both acute and delayed	May cause drowsiness / dizziness.
· Indication of any immediate medical	
attention and special treatment	
needed	No further relevant information available.
5 Fire-fighting measures	
 Extinguishing media 	
Suitable extinguishing agents	CO2, extinguishing powder or water spray. Fight larger fires with water spray of
	alcohol-resistant foam.
· For safety reasons unsuitable	
extinguishing agents	Water with a full water jet.
• Special hazards arising from the	
substance or mixture	In the event of a fire may be released:
	Nitrogen oxides (NOx)
	Under certain fire conditions, traces of other toxic substances cannot be excluded.
 Advice for firefighters 	
 Protective equipment: 	Put on breathing apparatus.
	Do not inhale explosion gases or combustion gases.

 Personal precautions, protective
equipment and emergency
procedures

· Environmental precautions:

Wear protective equipment. Keep unprotected persons away.



Do not allow to enter drains or water courses.

Prevent material from reaching sewage system, holes and cellars. Inform respective authorities in case product reaches water or sewage system.

• Methods and material for	- y
containment and cleaning up:	Absorb with liquid-binding material (sand, diatomaceous earth, acid binders, universal binders, sawdust).
	Dispose of contaminated material as waste according to section 13. Ensure adequate ventilation.
· Reference to other sections	See Section 7 for information on safe handling See Section 8 for information on personal protection equipment. See Section 13 for information on disposal.

· Protective Action Criteria for Chemicals

· PAC-1:		
64-17-5	ethanol	1,800 ppm
64742-49-0	Naphtha (petroleum), hydrotreated light (Note P)	1,000 mg/m³
· PAC-2:		
64-17-5	ethanol	3300* ppm
64742-49-0	Naphtha (petroleum), hydrotreated light (Note P)	11,000 mg/m³
· PAC-3:		
64-17-5	ethanol	15000* ppm
		(Contd. on page 4
		110



Page 4/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

rada nama taga 60450		
ade name tesa 60152		
		(Contd. of page
64742-49-0 Naphtha (petroleum), hy	drotreated light (Note P)	66,000 mg/m
Handling and storage		
Handling		
Precautions for safe handling	Ensure good ventilation/exhaustion at the workplace.	
Information about protection	Prevent formation of aerosols.	
against explosions and fires:	\frown	
	Keep ignition sources away - Do not smoke.	
	Protect against electrostatic charges.	
	Handle only outside or in explosion protected rooms.	
	Fumes can combine with air to form an explosive mixture.	
Conditions for safe storage, includ	ing any incompatibilities	
Storage Requirements to be met by		
storerooms and containers:	Store in cool location.	
Information about storage in one		
common storage facility:	void	
Further information about storage	void	
conditions:	Keep container tightly sealed.	
	Store in cool, dry conditions in well sealed containers.	
	Store only outside or in explosion proof rooms. Storing flammable liquids the Nationonal regulations have to be fulfilled	41
· Specific end use(s)	No further relevant information available.	
Exposure controls/personal pro	otection	
Additional information about desig	n	
of technical systems:	No further data; see item 7.	
Control parameters		
Components with critical values		
that require monitoring at the		
workplace:	The following constituent is the only constituent of the product which or other recommended exposure limit.	nas a PEL, T
	At this time, the remaining constituent has no known exposure limits.	
64-17-5 ethanol		
PEL Long-term value: 1900 mg/m ³ ,	1000 ppm	
REL Long-term value: 1900 mg/m ³ ,	1000 ppm	
TLV Short-term value: 1000 ppm		
A3	The lists that were valid during the compilation were used as basis.	
 Exposure controls Personal protective equipment 		
· General protective and hygienic		
measures	The usual precautionary measures should be adhered to in handling th	e chemicals.
	Keep away from foodstuffs, beverages and food.	
	Instantly remove any soiled and impregnated garments. Wash hands during breaks and at the end of the work.	
		Contd. on page



Page 5/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

	(Contd. of page
	Avoid contact with the skin.
	Avoid contact with the eyes and skin.
Breathing equipment:	filter A
	In case of brief exposure or low pollution use breathing filter apparatus. case of intensive or longer exposure use breathing apparatus that independent of circulating air.
Protection of hands:	Protective gloves.
	The glove material has to be impermeable and resistant to the product/
	substance/ the preparation.
	Selection of the glove material on consideration of the penetration tim
	rates of diffusion and the degradation
Material of gloves	Polyethylene
	Use solvent resistant gloves.
	Suitability and resistance of a glove depend on the conditions of use, such frequency and duration of contact, chemical resistance of the glove material, thickne and fit of the gloves. As a general rule, the glove manufacturer should be consulted the necessary information. Contaminated or damaged gloves should be replace immediately.
Penetration time of glove material	The exact breakthrough time must be obtained from the protective glove manufactu
	and must be observed.
Eye protection:	Safety glasses recommended during refilling.
	(() Safety glasses
Physical and chemical propertie	2
Filysical and chemical propertie	5
Information on basic physical and o	shamical properties

· General Information	
· Appearance:	
Form:	Liquid
Colour:	Without color / not defined
· Smell:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Not determined
Boiling point/Boiling range:	60 °C (140 °F)
· Flash point:	-25 °C (-13 °F)
· Inflammability (solid, gaseous)	Not applicable.
· Auto igniting:	245 °C (473 °F)
· Decomposition temperature:	Not determined.
· Self-inflammability:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/steam mixtures is possible.
	(Contid on page 6

(Contd. on page 6)



Page 6/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

Trade name tesa 60152

	(Contd. of page 5)
 Critical values for explosion: 	
Lower:	1 Vol %
Upper:	15 Vol %
Steam pressure at 20 °C (68 °F):	350 hPa (262.5 mm Hg)
· Density	Not determined
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
 Solubility in / Miscibility with 	
Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
dynamic:	Not determined.
kinematic:	Not determined.
· Solvent content:	
Organic solvents:	90.0 %
Solids content:	10.0 %
· Other information	No further relevant information available.

*10 Stability and reactivity

 Reactivity Chemical stability Thermal decomposition / conditions 	No further relevant information available.
to be avoided:	No decomposition if used according to specifications.
 Possibility of hazardous reactions 	No dangerous reactions known
· Conditions to avoid	No further relevant information available.
 Incompatible materials: 	No further relevant information available.
Hazardous decomposition	
products:	No dangerous decomposition products known

*11 Toxicological information

 Information on toxicological ef Acute toxicity: 	ffects
· LD/LC50 values that are releva	Int for classification:
ATE (Acute Toxicity Estimate)	
Inhalative LC50/ 4 h 120 mg/l (I	Rat)
Primary irritant effect:	
on the skin:	Irritant for skin and mucous membranes.
· on the eye:	No irritant effect.
Sensitization:	No sensitizing effect known.
• Additional toxicological	
information:	The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version: Irritant
	(Contd. on page 7)

(Contd. on page 7)



Page 7/11

1

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Trade name tesa 60152

· Carcinogenic categories

IARC (International Agency for Research on Cancer)

64-17-5 ethanol

• NTP (National Toxicology Program) None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity	
· Aquatic toxicity:	No further relevant information available.
· Persistence and degradability	No further relevant information available.
· Behaviour in environmental system	
· Bioaccumulative potential	No further relevant information available.
· Mobility in soil	No further relevant information available.
· Ecotoxical effects:	
· Remark:	Toxic for fish
• Additional ecological information:	
• According to recipe contains the	
following heavy metals and	
compounds according to EC	free of heavy metals (Ph. Od. Lin. CrC.)
guideline NO. 76/464 EC:	free of heavy metals (Pb, Cd, Hg, Cr6+) Free of Polybrominated Biphenyls (PBBs) and Polybrominated Diphenyl Ethers
	(PBDEs) according to RoHS Directive.
· General notes:	Also poisonous for fish and plankton in water bodies.
General notes.	Toxic for aquatic organisms
	Do not allow undiluted product or large quantities of it to reach ground water, water
	bodies or sewage system.
	Water hazard class 2 (Self-assessment): hazardous for water.
	Do not allow product to reach ground water, water bodies or sewage system.
	Danger to drinking water if even small quantities leak into soil.
· Results of PBT and vPvB assessme	
· PBT:	Not applicable.
· vPvB:	Not applicable.
· Other adverse effects	No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Uncleaned packagings:

· Recommendation



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

Must be specially treated under adherence to official regulations.

Uncleaned packaging must be disposed of in consultation with the regional waste disposal company.

(Contd. on page 8)

_____US __

(Contd. of page 6)

Reviewed on 03/10/2023



Page 8/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Trade name tesa 60152

Reviewed on 03/10/2023

(Contd. of page 7)

DOT, ADR, IMDG, IATA UN1993 UN proper shipping name Flammable liquids, n.o.s. (64742-49-0 Naphtha (petroleum hydrotreated light (Note P), Ethanol) ADR FLAMMABLE LIQUID, N.O.S. (64742-49-0 Naphtha (petroleum), hydrotreated light (Note P), ETHANOL (ETH ALCOHOL)), ENVIRONMENTALLY HAZARDOUS, (vapor pressure at 50°C not more than 110 kPa) IMDG FLAMMABLE LIQUID, N.O.S. (64742-49-0 Naphtha (petroleum), hydrotreated light (Note P), ETHANOL (ETH ALCOHOL)), ENVIRONMENTALLY HAZARDOUS, (vapor pressure at 50°C not more than 110 kPa)		
DOT Flammable liquids, n.o.s. (64742-49-0 Naphtha (petroleum) hydrotreated light (Note P), Ethanol) FLAMMABLE LIQUID, N.O.S. (64742-49-0 Naphtha (petroleum), hydrotreated light (Note P), ETHANOL (ETHANOL), INDER IMDG IMDG IMDG IMDG IATA Class Class Class Label Class S Inflammable liquids 3 (F1) Inflammable liquids 3 Inflammable liquids	UN-Number DOT, ADR, IMDG, IATA	UN1993
ADR FLAMMABLÉ LÍQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL (ETH ALCOHOL)). ENVIRONMENTALLY HAZARDOUS, (vap pressure at 50°C not more than 110 kPa) IMDG FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL (ETH ALCOHOL), MARINE FOLLUTANT IATA FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL) Transport hazard class(es) DOT IATA FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL) Class 3 Inflammable liquids Label 3 ADR S IATA S IMDG S Class 3 Inflammable liquids Label 3 IMDG S IMDG S IMDG S Import hazard class(es) S Class 3 Inflammable liquids ADR S Import for the set of the set o	UN proper shipping name DOT	Flammable liquids, n.o.s. (64742-49-0 Naphtha (petroleur
IMDG FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL (ETH ALCOHOL)), MARINE POLLUTANT IATA FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL) Transport hazard class(es) DOT Image: Class (Class (Clast) (Class (Class (Class (Clast (Class (Class (Class (Cla	ADR	FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL (ETH ALCOHOL)), ENVIRONMENTALLY HAZARDOUS, (vapo
Image: constraint of the constraint	IMDG	FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL (ETH ALCOHOL)), MARINE POLLUTANT
DOT V Class Label 3 ADR V Class Label 3 IMDG Class 3 Label 3 IMDG Class 3 IMDG Class 3 IMIDG Class 3 IMIDG IMID IMIDG IMIDG IMID IMIDG IMID IMID IMIDG IMID		FLAMMABLE LIQUID, N.O.S. (64742-49-0 Napht (petroleum), hydrotreated light (Note P), ETHANOL)
Class 3 Inflammable liquids Label 3	Transport hazard class(es)	
Label 3 ADR Class 3 (F1) Inflammable liquids 3 IMDG Class 2 IMDG Class 3 IMDG Class 3 IMDG	DOT	
Label 3 ADR Image: Class Label IMDG Image: Class Label Image: Class Label Image: Class Label Image: Class Label Class Label Image:		
Class 3 (F1) Inflammable liquids Label 3 IMDG 3 IMDG 3 Class 3 Inflammable liquids Label 3 IATA 3 Class 3 Inflammable liquids 3 3		
Class 3 (F1) Inflammable liquids Label 3 IMDG 3 IMDG 3 Class 3 Inflammable liquids Label 3 IATA 3 Class 3 Inflammable liquids 3 3	ADR	
Label 3 IMDG Class 3 Inflammable liquids Label 3 IATA Class 3 IATA		
Class 3 Inflammable liquids Label 3 IATA		
Class 3 Inflammable liquids Label 3 IATA	IMDG	
Label 3 IATA Class 3 Inflammable liquids		
IATA Class 3 Inflammable liquids		
Class 3 Inflammable liquids		~
Label 3		3 Inflammable liquids
	Label	3



Page 9/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

Trade name tesa 60152	
-----------------------	--

	(Contd. of page 8
· Packing group · DOT, ADR, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances 64742-49-0 Naphtha (petroleum), hydrotreated light (Note P)
Marine pollutant:	Yes Symbol (fish and tree) Symbol (fish and tree)
Special precautions for user Kemler Number:	Warning: Inflammable liquids 33
· EMS Number:	55 F-E,S- <u>E</u>
Stowage Category	B
Transport in bulk according to Annex II of MARPO	L73/78
and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
Remarks:	Special marking with the symbol (fish and tree).
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IMDG · Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (VAPOUR PRESSURE AT 50°C NOT MORE THAN 110 KPA) (64742-49-0 NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (NOTE P) ETHANOL (ETHYL ALCOHOL)), 3, II, ENVIRONMENTALLY HAZARDOUS

^{*}15 Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture
 Hazardous Air Pollutants

 None of the ingredients is listed.
 Cancerogenity categories
 TLV (Threshold Limit Value)
 64-17-5 ethanol
 MAK (German Maximum Workplace Concentration)
 64-17-5 ethanol
 NIOSH-Ca (National Institute for Occupational Safety and Health)
 None of the ingredients is listed.



Page 10/11

(Contd. of page 9)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Reviewed on 03/10/2023

Trade name tesa 60152

· National regulations

· Information about limitation of use: Employment restrictions concerning young persons must be observed.

 Decree to be applied in case of technical fault:

Critical quantity values according to the regulations on accidents should be adhered to.

• Technical instructions (air):

Class	Share in %
	45.0
NK	45.0

• Other regulations, limitations and prohibitive regulations

· TSCA	
64-17-5 ethanol	
64742-49-0 Naphtha (petroleum), I	nydrotreated light (Note P)
· SARA Section 313	
-	
· SARA section 355	
-	
 Proposition 65 - Cancer 	
-	
· Chemical safety assessment:	A Chemical Safety Assessment has not been carried out.

16 Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing data specification sheet: tesa SE, Corporate Regulatory Affairs Contact: tesa SE, Corporate Regulatory Affairs, Email: SDS@tesa.com, Tel.: +4940-88899-0 · Date of preparation / last revision 03/10/2023 RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer Abbreviations and acronyms: (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation - Category 2 Carcinogenicity 1A: Carcinogenicity - Category 1A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Aspiration Hazard 1: Aspiration hazard – Category 1



Page 11/11

Safety Data Sheet acc. to OSHA HCS

Printing date 03/10/2023

Trade name tesa 60152

• * Data compared to the previous version altered.

Reviewed on 03/10/2023

(Contd. of page 10)

-US ---