




# tesa® EasySplice 51457 LabellLine Heat



## Product Information

Double-sided splicing tape

## Product Description

tesa® 51457 EasySplice LabellLine Heat is a double-sided integrated flying splice tape consisting of a flat-back paper and a modified acrylic adhesive.

tesa® 51457 EasySplice LabellLine Heat features especially:

- Very high shear resistance on paper substrates
- Very good tack properties
- Very good adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing

Following functions are provided:

- Slit liner for the secure fixation of the top sheet
- Adhesive formulation with very high shear resistance for excellent holding power between expiring web and new reel
- One splitting strip with paper backing for a smooth opening of the new paper reel without jeopardising the coating process

Color: Blue

## Application Fields

tesa® 51457 EasySplice LabellLine Heat is particularly suitable for:

- Flying splices of paper faces and backings in the label stock industry at splicing speeds <600m/min.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                      |                   |        |
|--------------------|----------------------|-------------------|--------|
| • Backing          | Paper                | • Total thickness | 100 µm |
| • Type of adhesive | tackified acrylic    | • Color           | blue   |
| • Type of liner    | bi-siliconised paper |                   |        |

## Properties/Performance Values

- |                       |     |                    |         |
|-----------------------|-----|--------------------|---------|
| • Elongation at break | 6 % | • Tensile strength | 30 N/cm |
|-----------------------|-----|--------------------|---------|

For latest information on this product please visit <http://l.tesa.com/?ip=51457>



# tesa<sup>®</sup> EasySplice 51457 LabelLine Heat

Product Information

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51457>