



tesa® Professional 60760 Marking Tape



Product Information

Floor marking tape / hazard tape

Product Description

tesa® 60760 is a hazard tape intended for temporary use. The tower includes 6 rolls. While the substrate material is soft PVC, the modified adhesive is made of natural rubber for good adhesive strength and reliable adhesion to the surface underneath. The abrasion-proof hazard tape, which can be torn by hand, is also suited to rough surfaces and is a valuable aid when marking hazards on building sites or in workshops.

Application Fields

- Temporary marking applications
- Identify and mark mobile and stationary objects
- Adhesion on many different surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-----------|
| • Backing material | soft PVC | • Total thickness | 150 µm |
| • Type of adhesive | natural rubber | • Colour | litho-red |

Properties/Performance Values

- | | | | |
|-----------------------------------|---------|-------------------------------|--------|
| • Elongation at break | 220 % | • Straight tear edges | medium |
| • Tensile strength | 33 N/cm | • Suitable for rough surfaces | good |
| • Ageing resistance (UV) | low | • Tack | good |
| • Humidity resistance | good | • Water resistance | medium |
| • Static shear resistance at 23°C | good | | |

Adhesion to Values

- | | |
|-------------------|--------|
| • Steel (initial) | 2 N/cm |
|-------------------|--------|



tesa[®] Professional 60760 Marking Tape

Product Information

Additional Information

tesaflex[®] 60760 is also available with two highly visible colour-modes which accord to safety-regulations.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60760>