



tesa[®] 4319

Product Information



Strongly crêped paper masking tape for painting and packaging

Product Description

tesa[®] 4319 is a highly crêped, general purpose paper masking tape for various application fields.

Sustainable Aspects

67% bio-based content in total product excluding liner (by weight)



For more information: <https://www.tesa.com/product-sustainability>

Product Features

- The high elongation of the crepe backing makes it suitable especially for 3-dimensional objects.
- Thanks to the thick adhesive layer, the masking tape holds reliably even on rough surfaces.
- The strong and conformable paper backing of tesa[®] 4319, makes it suitable even for more like applications surface protection where a high mechanical resistance is needed.
- The flexible masking tape saves you corrections that are time-consuming.
- With the combination of high-quality surface protection tape and sound workmanship, you will achieve optimum working results.

Application Fields

It is particularly suited for masking during paintwork, for underbody sealing and bundling as well as for edge protection of paper reels. The product offers a good tack.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|--|--------|
| • Backing material | highly-creped paper | • Bio-based content of liner by weight (acc. EN 16785) | 67 % |
| • Type of adhesive | natural rubber | • Total thickness | 375 µm |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|-----------|
| • Elongation at break | 58 % | • Hand tearability | very good |
| • Tensile strength | 24 N/cm | • Suitable for rough surfaces | very good |

For latest information on this product please visit <http://l.tesa.com/?ip=04319>



tesa[®] 4319

Product Information

Adhesion to Values

- steel 4.5 N/cm

Additional Information

Recommendation:

Stretching the crêped backing guarantees evenly defined paint edges and a good adhesion.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04319>