



tesa® Professional 4306 Pro PLUS Painter's Tape



Product Information

Premium Painters tape for indoor painting applications

Product Description

The very name of tesa® 4306 painters tape makes its standard quite clear and its outstanding adhesion results in sharp paint and varnish edges. This high-quality paper masking tape makes both clean and convenient painting work possible, because the extremely flat but high tear-resistant paper backing and simple unrolling make it extremely easy to use. In addition, this premium painters tape helps you avoid time-consuming and expensive touching-up work. As a professional aid, the innovative paper masking tape is a reliable partner for painting work of all kinds.

Application Fields

- Suitable for all kind of painting and masking applications
- Indoor masking (up to 14 days)
- Outdoor masking (up to 3 days)
- Masking for straight line and slight curves

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|------------|
| • Backing material | Washi paper | • Total thickness | 95 µm |
| • Type of adhesive | natural rubber | • Colour | pale cream |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|-----------|
| • Elongation at break | 7 % | • Hand tearability | very good |
| • Tensile strength | 37 N/cm | • Suitable for rough surfaces | good |

Adhesion to Values

- | | |
|---------|--------|
| • steel | 2 N/cm |
|---------|--------|



tesa[®] Professional 4306 Pro PLUS Painter's Tape

Product Information

Additional Information

The natural rubber adhesive is generally not UV resistant. tesa[®] 4306 should therefore not be used for more than 3 days outdoors

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04306>