

tesa® Powerstrips 58060

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	•	Holding power up to	2 Kg
•	Total thickness	650 μm	•	Hook shape	_NULL
•	Holding power of strip up to	2 Kg	•	Silicone free	yes

Properties/Performance Values

•	Ageing resistance (UV) Application temperature from Applicationfield	yes -15 °C Kitchen, Living room, Office, Hall, Children's room, Bathroom	•	Residue free removal Reusable Reusable with Solvent free Suitable surfaces	yes no _NULL yes Even wood, Tiles,
•	Area of use	Indoor			Most plastics, Glass,
•	Batteries included	no			Acrylic glass, Steel,
•	Batteries required	no			Metal
•	Chemical resistance	no	•	Temperature resistance	no
•	Hazard material	no	•	Temperature resistance max.	35 °C
•	Humidity resistance	no	•	Temperature resistance min.	5 °C
•	Material	_NULL	•	UV-resistant	no
•	Oil and grease resistance	no	•	Water resistance	no
•	Ozone resistance	yes	•	Waterproof	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

