

tesa® Powerstrips 58810

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Type of adhesive	synthetic rubber	•	Holding power up to	1 Kg
•	Total thickness	650 μm	•	Hook shape	_NULL
٠	Holding power of strip up to	1 Kg	٠	Silicone free	yes

Properties/Performance Values

 Ageing resistance (UV) Application temperature Applicationfield 	yes from -15 °C Kitchen, Living room, Children's room, Office, Hall, Bathroom	 Ozone resistance Residue free removal Reusable Reusable with Solvent free 	yes yes no _NULL yes
 Area of use 	Indoor	 Suitable surfaces 	Even wood, Tiles,
 Batteries included 	no		Most plastics, Glass,
 Batteries required 	no		Acrylic glass, Steel,
Chemical resistance	no		Metal
 Hazard material 	no	• Temperature resistance max.	35 °C
Humidity resistance	no	• Temperature resistance min.	5 °C
Material	_NULL	UV-resistant	yes
• Oil and grease resistance	e no	Water resistance	no
		Waterproof	no

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



²age 1 of 1 – as of 23/09/24 – en-ZA