

tesa® ACXplus 7055

Product Information



ACX^{plus} High Transparency 1000μm

Product Description

tesa® ACX^{plus} 7055 is a transparent acrylic core tape. It consists of a high-performance acrylic system and is primarily characterised by its Bonding Power, Stress Dissipation and its Temperature and Weather Resistance.

Due to the high transparency it is especially suitable for constructive bonding of transparent and translucent materials such as glass or acrylic.

The visco-elastic, solid acrylic core compensates different thermal elongation of bonded parts.

Application Fields

Bonding of transparent and translucent materials in the following Industries:

- · Sign manufacturing
- · Deco Glass Panels
- · Partition Walls

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	solid acrylic	•	Total thickness	1000 µm
•	Type of adhesive	pure acrylic	•	Colour	transparent
•	Type of liner	silicone-free film			

Adhesion to Values

• Steel (after 3 days) 24 N/cm

Additional Information

PV 22 = White PE coated paper liner tesa® ACX^{plus} branded PV 24 = Blue HDPE filmic liner



tesa® ACXplus 7055

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

