




tesa® EasySplice 51100 PrintLine



Product Information

Multifunctional splicing tape

Product Description

tesa® EasySplice 51100 PrintLine is a multifunctional flying splice tape consisting of a flat-back paper and a repulpable acrylic adhesive.

tesa® EasySplice 51100 PrintLine features especially

- Very high tack properties
- High shear resistance
- Very good adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing
- Smooth and easy application due to flexible backing

Colour: Blue

Application Fields

tesa® EasySplice 51100 PrintLine is particularly suitable for:

- Flying splices in the printing industry on most paper grades as well as belt-driven machines
- Use in conjunction with tesa EasyBridge for superior belt-covering
- Special splitting strip with opening characteristics tailored to belt-driven machines, for a smooth opening of the new paper reel without jeopardizing the printing process

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Total thickness 100 µm

Properties/Performance Values

- Elongation at break 6 %
- Tensile strength 30 N/cm
- Shelf life time (packed) < 25°C 12 months

For latest information on this product please visit <http://l.tesa.com/?ip=51100>



tesa[®] EasySplice 51100 PrintLine

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51100>