



tesa® Powerbutton Universal Hook S

Product Information

BNR 59320

Product Description

The tesa® Powerbutton Universal hook Small is a water- and heat-resistant chrome hook designed for damage-free mounting without drilling.

Product Features

- Easy application without drilling, screws or nails
- Extra-strong hold up to 5kg
- Usable on and removable from most surfaces***
- Strong hold on most surfaces**
- Waterproof
- High temperature resistance
- Chrome Plated
- Made from steel
- Available as single hooks
- Hooks reusable with the tesa® Powerbutton technology

**Does not hold Plaster, Wallpaper, PE, PTFE or PP

***Not removable from Plaster or Wallpaper. Residues might remain

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|-------------------------|--------------|-------|
| • Type of adhesive | Silane modified polymer | • Hook shape | Round |
| • Holding power up to | 5 Kg | | |



tesa® Powerbutton Universal Hook S

Product Information

Properties/Performance Values

• Application temperature from	+15 °C	• Material	Chromed metal
• Application temperature to	+30 °C	• Residue-free removability	yes
• Applicationfield	Bathroom, Kitchen	• Reusable	yes
• Area of use	Indoor	• Solvent free	yes
• Batteries included	no	• Suitable surfaces	Glazed Tiles, Marble, Glass, Metal, Stone, Concrete, Even wood, Most plastics
• Batteries required	no		
• Chemical Resistance	no	• UV resistant	yes
• Hazard material	no	• Waterproof	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>