



tesa® Powerstrips Vario-Curtain Hook

Product Information

BNR 58034, 58047

Product Description

These self-adhesive tesa Powerstrips Curtain Hooks are perfect to fasten any standard kitchen or bathroom curtain to a window frame without drilling holes.

Product Features

- Two-in-one hook is suitable for most types of net curtain rail for fixing or hanging
- Holds all standard types of net curtain rail up to 1 kg
- Removable without trace thanks to tesa Powerstrips® technology
- Applied in a jiffy, leaves no unsightly drill or nail holes
- Curtain rail hook reusable with tesa Powerstrips SMALL
- Completely covered tesa Powerstrip®

Application Fields

- How to apply - Step by step
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply the Powerstrip Small strip on the surface - press for 5 seconds minimum
 3. Open the hook and stick the back of the hook onto the strip - press for 5 seconds minimum
 4. Close and snap-lock the hook.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|-----------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 1 Kg | • Silicone free | yes |



tesa® Powerstrips Vario-Curtain Hook

Product Information

Properties/Performance Values

• Ageing resistance (UV)	yes	• Ozone resistance	yes
• Application temperature from	-15 °C	• Residue-free removability	yes
• Applicationfield	Kitchen, Living room, Children's room, Office, Hall, Bathroom	• Reusable	yes
• Area of use	Indoor	• Reusable with	Powerstrips Small
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Suitable surfaces	Even wood, Tiles, Most plastics, Glass, Acrylic glass, Steel, Metal
• Chemical Resistance	no	• Temperature resistance	yes
• Hazard material	no	• Temperature resistance max.	35 °C
• Humidity resistance	no	• Temperature resistance min.	5 °C
• Humidity sealing	no	• UV resistant	no
• Material	PS (polystyrene)	• Water resistance	no
• Oil and grease resistance	no	• Waterproof	no

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>