



# tesa<sup>®</sup> extra Power Extreme Repair

## Product Information



BNR 56064

## Product Description

tesa Extreme repair is a self-bonding Repairing Tape to be used as a non conductive electrical tape or a plumbers tape for temporary tube and pipe repairs.

## Product Features

- 12 bar pressure-resistant
- UV-resistant
- Temperature-resistant between -60°C to +260°C
- Withstands electricity of 8000V

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- Backing Silicone • Total thickness 500 µm

## Properties/Performance Values

- |                                |                              |                               |  |
|--------------------------------|------------------------------|-------------------------------|--|
| • Tensile strength             | 33 N/cm                      | • Ozone resistance            | yes  |
| • Adhesive strength            | Very high adhesion           | • Residue-free removability   | yes  |
| • Ageing resistance (UV)       | yes                          | • Reusable                    | no   |
| • Application temperature from | -60 °C                       | • Solvent free                | yes  |
| • Application temperature to   | +260 °C                      | • Spare part service          | no   |
| • Applicationfield             | Home, Garden, Car,<br>Garage | • Suitable surfaces           | Even wood, Tiles,<br>Brick, Most plastics,<br>Glass, Acrylic glass,<br>Plaster, Metal, Steel,<br>Stone |
| • Area of use                  | Outdoor                      | • Tear resistance             | yes  |
| • Batteries included           | no                           | • Temperature resistance      | yes  |
| • Batteries required           | no                           | • Temperature resistance max. | 260 °C   |
| • Ecofriendly packaging        | no                           | • Temperature resistance min. | -60 °C   |
| • Hand tearability             | no                           | • Tensibility                 | 750 %  |
| • Hazard material              | no                           | • UV resistant                | yes  |
| • Humidity resistance          | yes                          | • Water resistance            | yes  |
| • Material                     | Silicone                     | • Waterproof                  | yes  |
| • Oil and grease resistance    | yes                          | • Writable                    | no   |

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>



# tesa<sup>®</sup> extra Power Extreme Repair

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>